



Trailed PNEUMATIC seed drill
Model SS P 45 T RC – 4,50 m

Seed drill
for direct sowing

SICURA Line SSM and SSP



Trailed MECHANICAL seed drill
Model SS M 30 T RP – 3,00 m

ma/ag
DIVISIONE SEMINATRICI



**SEED DRILL FOR DIRECT SOWING
TRAILED MECHANICAL VERSION
SICURA SSMT line**

Ideal for sowing both on till or no-till soil

- Steering towing beam (90°) swivelling
- Seed distributor for small and big seeds
- Adjustable dosage seed by cams in oil bath with inspection window
- Electronic hectare sensor
- Seed hopper with "reserve" indicator of 600 lt
- Manual device for calibration dosing seed
- Seed tray for calibration and discharge hopper
- Ladder and platform for loading/inspection hopper
- Hydraulic trailer for transport on road with 400/60-15.5 wheels
- Lighting and signs of obstruction



SICURA SEED ELEMENT

- Element with parallelogram, damped and adjustable
- Double discs (toothed/smooth) assembled in a staggered manner for opening housing seed, with cleaning soil scrapers
- Device for the insertion of the seed into the soil



- Group of closing and cover ring seed discs, mounted on supports with balancer, adjustable
- Possibility to increase the charge of the element by traction spring.

**MANUAL ADJUSTING WORKING DEPTH REGULATION,
BY SPECIAL LEVER**

SEED DRILL FOR DIRECT SOWING TRAILED PNEUMATIC VERSION SICURA SSPT line

Ideal for sowing both on till or no-till soil

- Steering towing beam (90°), hydraulically adjustable, with valve for blocking depth work and slot of oscillating
- Pneumatic, volumetric adjustable seed distributor group
- Automotive fan, hydraulic
- Electronic hectare sensor
- Automotive seed hopper with "reserve" indicator of 2500 lt
- Manual device for calibration dosing seed
- Seed tray for calibration and discharge hopper
- Ladder and platform for loading/inspection hopper
- Hydraulic central wheels with stop valve for the regulation of the working depth
- Lighting and signs of obstruction



Overall dimensions in transport 2,50 m

VERSION WITH MECHANICAL DISTRIBUTION, TRAILED, FIXED FRAME

MODEL	VERSION	WORKING W.	FRAME	TRANSP. W.	ROWS N.	SPACE DISTANCE mm	WEIGHT KG
SS M 30 T RP	TRAILED	m 3,00	FIXED	m 3,00	17	187,5	3100
SS M 30 T RC	TRAILED	m 3,00	FIXED	m 3,00	17	187,5	2980
SS M 40 T RC	TRAILED	m 4,00	FIXED	m 4,00	22	187,5	3650

RP = rear wheels RC = central wheels

VERSION WITH PNEUMATIC DISTRIBUTION, TRAILED, FOLDABLE FRAME TO 2,50 m

MODEL	VERSION	WORKING W.	FRAME	TRANSP. W.	ROWS N.	SPACE DISTANCE mm	WEIGHT KG
SS P 30 T RC	TRAILED	m 3,00	FIXED	m 3,00	17	187,5	3230
SS P 45 T RC	TRAILED	m 4,50	HYDRAULIC	m 2,50	25	187,5	4510
SS P 60 T RC	TRAILED	m 6,00	HYDRAULIC	m 2,50	33	187,5	6180

RP = rear wheels RC = central wheels



MADE IN ITALY



ma/ag

DIVISIONE SEMINATRICI

26011 CASALBUTTANO (Cremona) - ITALIA
 www.ma-ag.com - E-mail: info@ma-ag.com
 Head office and production: Via Giovanni Paolo II, 12
 Tel. +39 0374 363119 - Fax +39 0374 360406
 Administrative office: Via Bergamo, 7/b
 Tel. +39 0374 362680 - Fax +39 0374 362280

