

SUPER GRUBBER WITH ANCHORS

Light model – SEA L

NEW



ma/ag
MACCHINE AGRICOLE

STANDARD EQUIPMENT

- Brought on lift machine, ideal for breaking new round and for minimal working. Best results for horse power tractors within 70 and 140 hp.
- Frame built with steel tubular 100x100x8, maximal strength, adjustable, in order to assure the best strength.
- Anchors number variable from 5 to 7 according to working width and to Horse Power available. Anchors are arranged on 2 working rows.
- Steel anchor thickness 30 mm supplied with a cut-off device with a sharing screw. Interchangeable, reversible share, with anchor protection against wear. On the anchor it is possible to mount a couple of triangular shares.
- Couple of rubber wheels for the working depth regulation (at request)
- On the rear it is possible to equip the machine with spuntoni roller – double spuntoni roller
- Sub frame depth: 65 cm – depth working until 40 cm

BASE VERSION

MODEL	ANCHORS N.	W. WIDTH	TRANSP. W.	HP	KG
SEA L 20/5 B	5	2,00	2,00	70/90	590
SEA L 25/5 B	5	2,50	2,50	70/90	650
SEA L 25/7 B	7	2,50	2,50	90/110	780
SEA L 30/7 B	7	3,00	3,00	90/140	830

VERSION WITH SINGLE SPUNTONI ROLLER – DIAM. 140 MM – MANUAL REGULATION

MODEL	ANCHORS N.	W. WIDTH	TRANSP. W.	HP	KG
SEA L 20/5 RS	5	2,00	2,00	70/90	750
SEA L 25/5 RS	5	2,50	2,50	70/90	820
SEA L 25/7 RS	7	2,50	2,50	90/110	890
SEA L 30/7 RS	7	3,00	3,00	90/140	1050

VERSION WITH DOUBLE SPUNTONI ROLLER – DIAM. 140 MM – MANUAL REGULATION

MODEL	ANCHORS N.	W. WIDTH	TRANSP. W.	HP	KG
SEA L 20/5 RD	5	2,00	2,00	70/90	890

SEA L 25/5 RD	5	2,50	2,50	70/90	950
SEA L 25/7 RD	7	2,50	2,50	90/110	1080
SEA L 30/7 RD	7	3,00	3,00	120/140	1180

VERSION WITH REAR DISCS DIAM. 560X4,5 MM – MANUAL REGULATION

MODEL	ANCHORS N.	W. WIDTH	TRANSP. W.	HP	KG
SEA L 20/5 DIS	5	2,00	2,00	70/90	1070
SEA L 25/5 DIS	5	2,50	2,50	70/90	1150
SEA L 25/7 DIS	7	2,50	2,50	90/110	1280
SEA L 30/7 DIS	7	3,00	3,00	120/140	1390

ACCESSORIES	DESCRIPTION
ACSEA01	Couple of wheels for working depth regulation
ACSEA02	Couple of triangular share (each one)
ACSEA03	Rear hydraulic regulation for roller and discs
ACSEA04	Lateral steel hoop holding kit



ma/ag
MACCHINE AGRICOLE

SEA L 30/7 RD



ma/ag s.r.l.

26011 - CASALBUTTANO (CR) - ITALIA

C. Fisc. - P. IVA - C.C.I.A.A. : IT
01334790191

R.E.A. n° 162410 ma/ag S.r.l. - Cap. Soc. -
31 gennaio € 100'000,00 i.v.2016

Sede Legale e Produttiva:
Via Giovanni Paolo II, 12
Tel 0374.363119 - Fax
0374.360406

Sede Amministrativa:
Via Bergamo, 7/b
Tel 0374.362680 - Fax
0374.362280

Internet:

Web: www.ma-ag.com
E-mail: info@ma-ag.com